


L15-MB650®

High power 15" low frequency speaker
650 WATTS

- Excellent bass and mid-bass response, high power handling capacity.
- Aluminium die-cast frame with gold plated push type heavy duty terminals.
- GLASS FIBRE former for withstanding high temperature.
- 10.16 cm (4") Edge-wound aluminium wire voice coil for higher SPL.



| SPECIFICATIONS | L15-MB650® |
|------------------------------------|--------------------------|
| POWER RATING | 650W RMS/1300W Programme |
| NOMINAL DIAMETER | 380mm (15") |
| NOMINAL IMPEDANCE | 8Ω |
| SENSITIVITY (1W/1m) | 97dB |
| MAGNET WEIGHT | 2.85kg |
| RESONANT FREQUENCY (Fs) | 50Hz |
| DC RESISTANCE (Re) | 5.1Ω |
| ELECTROMAGNETIC Q (Qes) | 0.32 |
| MECHANICAL Q (Qms) | 5.91 |
| TOTAL Q (Qts) | 0.30 |
| COMPLIANCE EQUIVALENT VOLUME (VAS) | 109Litr |
| SURFACE AREA OF CONE (Sd) | 830cm ² |
| REFERENCE EFFICIENCY (ηo) | 3.5% |
| VOICE COIL | 4.0" |
| OVERHANG (Xmax) | 3.6 mm |
| MOVING MASS (Mms) | 97.60gm |
| BL PRODUCT (BL) | 22.92TM |
| COIL INDUCTANCE (Le) | 1.60mH |
| OVERALL DIAMETER | 390 mm |
| DEPTH | 142 mm |
| BAFFLE HOLE DIAMETER | 357 mm |
| BOLT MOUNT DIAMETER (PCD) | 372 mm (8 Bolts) |
| WEIGHT | 11.00kg |